

Semi-automatic intermediate proofer LTAS



The semi-automatic intermediate proofer with manual filling is designed for medium productions. It accepts as well as the pieces of dough for small breads that for big breads.

Characteristics

- Manual loading and automatic unloading
- **Intermediate proofer with gutters equipped with felts and velcro**
- Free selection by the operator of the number of pieces of dough per gutter
- Selector switch with 2 positions : manual loading or self emptying
- Auto-carrier frame made of steel coated, gutters shaped in « U » with rod of diameter 10mm
- **Rounder shelf**
- Germicide lamp

Ergonomics / Maintenance

- Use friendly: the control panel can be placed on the left (to be specified on order), or on the right. The time of loading corresponds to the time of loading by the operator + 3 seconds for the time of loading the gutter
- Easy maintenance thanks to the removable panels

Model	LTAS MANUELLE 2400	LTAS MANUELLE 2700
Loading	Manual	
unloading	Automatic	
Capacity / Production	Variable according to the using	
Number of gutters	77 of which 69 useful	87 of which 79 useful
Length of the gutters (in mm)	1600	1600
Flower machine with brush	Electric	
Rounder	Non	Non
Germicid lamp	2	2
POWER / TENSION		
Power (en kW)	1	
Tension	400V / TRI+N+T / 50Hz	
DIMENSIONS		
Width (in mm)	1880	1880
Height (in mm)	2400	2700
Depth(in mm)	2140	2140
Weight (in kg)	env. 800	env. 850

Non-binding document. LAMBERT MECANIQUE SAS reserves the right to modify its products without notice



LAMBERT MECANIQUE SAS - 4 Avenue Jean Monnet – 26000 VALENCE
 Phone : 0033 4 75 25 98 30 – Fax : 0033 4 75 83 95 23 - contact@lambert-mecanique.eu
 Internet site : <http://www.lambert-mecanique.eu>