

## Fork kneaders, removable bowl



The fork kneaders with removable bowl allow the transfer of the dough more easily until the bowl lifter thanks to their integrated transport trolley of the bowl. Besides, it facilitates the resting of the dough.

### Models

---

The fork kneaders with removable bowl are available in 3 versions. Each model distinguishes itself by its water capacity:

- Model **30JAC** : max. capacity **30 liters / 80 kg of dough**
- Model **45JAC** : max. capacity **45 liters / 120 kg of dough**
- Model **60JAC** : max. capacity **60 liters / 160 kg of dough**

### Features

---

- One-piece frame made of steel
- Kneading arm made of iron aluminium. Manual raising
- **Stainless steel removable bowl with rounded edges** braked by manual brake
- **2 electronic timers** with double digital display, directly programmable until 20 minutes. Reminder of the time programmed. It is possible to use only one timer in continuous with stop at the end of work. Besides, you also can obscure the timers for a continuous and unlimited work.
- 2 speeds on the 2 timers. Automatic passage of the 1<sup>st</sup> to the 2<sup>nd</sup> speed in AUTO mode
- Watertight control panel on frame
- Adjustable head in standard (revolving on 2 bearings)
- Safety stainless steel full cover with flap

## Ergonomics / maintenance

---

-**Safety retractable stainless steel full cover offering more place** : in open position, the whole bowl is available because the cover turns upside down by the rear.

## Options

---

- Added stainless steel bowl

<b>Models</b>	<b>30JAC</b>	<b>45JAC</b>	<b>60JAC</b>
Dough capacity (kg)	80	120	160
Dough capacity (mini/maxi in liters)	10/30	15/45	20/60
Flour capacity (mini/maxi in kg)	18,7/50	25/75	33/100
<b>KNEADING ARM</b>			
1st speed	48 rotations per minute loaded		
2 <sup>nd</sup> speed	72 rotations per minute loaded		
<b>STAINLESS STEEL BOWL</b>			
Capacity (liters)	170	230	330
Bowl diameter (mm)	800	900	1000
Bowl brake	Manual		
<b>ELECTRICALS</b>			
Maximum power (in 2 <sup>nd</sup> speed) (kW)	5,5		
Voltage (V)	Three-phases 400V+N+G		
<b>DIMENSIONS</b>			
Width (mm)	1260	1360	1460
Height (mm)	1295		
Depth (mm)	1130	1155	1180
Depth with cover open (mm)	1270	1295	1320
Weight (kg)	500	520	540

*Non-contractual specifications and illustrations - LAMBERT MECANIQUE SAS reserves the right to modify specifications without prior notice*

